

Automatic Butt Fusion Machine	Applicable Pipe Diameter	Temperature Control Range	Temp. deviation in surface	Power/Voltage of Control Box	Power/Voltage of Heating Plate	Power/Voltage of Trimmer	Docking Deviation	Ambient Temperature	Time for Welding Temperature
JQA160	63mm-160mm	0-270°C	±7°C	0.75KW/220V	1.6KW/220V	1.2KW/220V	≤0.2MM	-5~40°C	<20mins
JQA200	63mm-200mm	0-270°C	±7°C	0.75KW/220V	1.6KW/220V	1.2KW/220V	≤0.2MM	-5~40°C	<20mins
JQA250	90mm-250mm	0-270°C	±7°C	0.75KW/220V	2.5KW/220V	2.5KW/220V	≤0.2MM	-5~40°C	<20mins
JQA315	90mm-315mm	0-270°C	±7°C	0.75KW/220V	3KW/220V	2.5KW/220V	≤0.2MM	-5~40°C	<20mins
JQA355	90mm-355mm	0-270°C	±7°C	0.75KW/220V	3.5KW/220V	2.5KW/220V	≤0.2MM	-5~40°C	<20mins
JQA400	110mm-400mm	0-270°C	±7°C	0.75KW/220V	5.1KW/220V	1.5KW/220V	≤0.2MM	-5~40°C	<20mins
JQA450	180mm-450mm	0-270°C	±7°C	0.75KW/220V	5.2KW/220V	1.5KW/220V	≤0.2MM	-5~40°C	<20mins
JQA500	180mm-500mm	0-270°C	±7°C	0.75KW/220V	8KW/220V	1.5KW/220V	≤0.2MM	-5~40°C	<20mins
JQA630	315mm-630mm	0-270°C	±7°C	0.75KW/380V	9.2KW/380V	1.5KW/380V	≤0.2MM	-5~40°C	<20mins